



SECUFIRE® P Steel tubular frame door

Smoke protection combined with certified high security

The SECUFIRE® P is a smoke protection door designed for areas where controlled smoke management and additional security requirements must be met simultaneously. It combines certified smoke resistance with burglary and ballistic protection, making it ideal for secure interior areas where transparency and safety are both important.

Thanks to its slim steel tubular frame construction, the door can be flexibly integrated into architectural concepts – either as a standalone door or as a transparent complement to adjacent high-security elements. The construction ensures high mechanical stability with narrow sightlines, providing an important function in both organisational and structural fire protection.



SECUFIRE® P steel tubular frame door

Highlights

- Smoke protection focused: Certified smoke resistance for secure interior areas – ideal for zones requiring safe escape routes and clear compartmentalisation.
- Security included: Tested burglary resistance up to RC3/RC4 (depending on configuration) and ballistic resistance up to FB4-NS, allowing use where additional threats must be considered.
- Architectural adaptability: Slim profiles, concealed glazing beads, flexible lock and hardware configurations enable a harmonious appearance – also in combination with other security and glazing elements.

Security features



Forced entry resistance

RC1 RC2 RC3 RC4 RC5 RC6
DIN EN 1627-1630



Bullet resistance

FB1 FB2 FB3 FB4 FB5 FB6 FB7
DIN EN 1522 + 1523



Explosion and shock wave

EXR1 EXR2 EXR3 EXR4 EXR5
DIN EN 13123-2 + 13124-2



Fire and smoke protection

EI15 EI20 EI30 EI45 EI60 EI90 EI120 EI180 EI240
Fire protection DIN EN 13501-2
S_a S₂₀₀
Smoke protection DIN EN 1643-1

Properties



Air permeability class N/A



Wind load resistance class N/A



Sound insulation up to R_w 42 dB



Mechanical durability class C5



Water tightness class N/A



Sash dimension up to 1.510 × 2.510 mm (W x H)



Impact resistance class N/A




Sash weight up to 400 kg



U_D-value N/A

Design examples



More Sälzer
security doors



Architectural sections
available upon request